

Stain Removers

## **NO RUG**

## Rust Stain Remover for Granite, Porcelain, Quartz, and all Acid Resistant Materials

**NO RUG** is a rust stain remover formulated for all acid-resistant surfaces. The product is highly effective against salt efflorescences and oxidations. Its formula allows the product to penetrate deeply into the material allowing the removal of deep stains.

BENEFITS	<ul> <li>✓ Water-based</li> <li>✓ Acid pH</li> <li>✓ Deep penetrating action</li> <li>✓ Great extractive power</li> </ul>
USES	<b>Suitable for</b> indoor and outdoor application. <b>Suitable for</b> Quartz resin agglomerate, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Glazed ceramic, Clinker, Terracotta, Granite, Polished porcelain stoneware, Natural porcelain stoneware, Structured porcelain stoneware, Facing brick, Reconstructed stone (Eco stone), Porphyry, Quartzite, Terracotta, Tuff. <b>Not suitable</b> for materials sensitive to acids.
APPLICATION EQUIPMENT	Porduct application: Brush, Spatula, Direct application
APPLICATION STEPS	<ul> <li>Surface Preparation</li> <li>Thoroughly clean the surface making sure to remove all dust and dirt</li> <li>Do not apply NO RUG on heated surfaces. Make sure to apply the product during the coolest times of day.</li> <li>If the surface to be treated has been previously waxed or treated we recommend removing them by dewaxing the surface.</li> <li>NO RUG can only be mixed with FABER POULTICE and no other product.</li> <li>Apply NO RUG on surfaces with a temperature between +5 and +40°C</li> <li>Protect all areas, not to be treated</li> </ul>
	<b>Application</b> Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.
	<ul> <li>The product is ready to use. Apply the product on the stain using the preferred tool making sure to evenly cover the whole affected area.</li> <li>Let the product act on the stain until it is completely gone. The action time depends on the material, how stubborn and old the stain is. It is hard to define how long it will take to remove the stain.</li> <li>We always recommend taking a preliminary test to evaluate how long the product needs to act in order to remove the stain. Here is an overview on the action time of the product:</li> </ul>

 $_{\odot}$  For superficial rust stains on compact and low-absorbing materials the action time is between 30 and 60 minutes.

 $\circ$  For deeper rust stains on porous materials, the action time is between 1 hour and 4 hours.

	#FABERSURFACECARE
	MADE4STONE TILE & STONE CARE
	<ul> <li>For very deep and stubborn stains on very absorbing materials the action time is between 8 hours and 24 hours.</li> </ul>
	<ul> <li>If the stain removal process requires a long action time we recommend covering the area with plastic. It is also important to carefully cover the stain to avoid it drying to quickly. If the product has been covered during the application, it is important to remove the cover and to let the surface exposed for at least 30 to 60 minutes before removing the residues and rinsing the surface.</li> <li>Once the action time has passed make sure to remove the residues. To remove NO RUG use cloths and paper towels for small areas. For larger areas, we recommend using a mop. Once the residues are gone make sure</li> </ul>
	<ul> <li>to thoroughly rinse the surface with clean water.</li> <li>Wait for the surface to dry completely before evaluating the achieved result.</li> <li>If the stains persists we recommend repeting the application or grinding the surface as a preliminary step before the application of NO RUG.</li> <li>To remove very stubborn and deep rust stains we recommend to grind the</li> </ul>
	surface first in order to increase the absorption degree of the material.
MAINTENANCE PRODUCTS	<ul> <li>Resume surface use after 2-3 hours from the application.</li> <li>For the daily cleaning of a surface treated with NO RUG we recommend: NEUGEL or ALGAFLOOR depending on the material</li> <li>For the heavy-duty cleaning of a surface treated with NO RUG we recommend: FABER 30 o DETERFUG depending on the material</li> <li>Following the removal of the stain we recommend applying a water-resistant treatment to choose depending on the material.</li> </ul>
INSTRUCTIONS AND GUIDELINES	<ul> <li>NO RUG can only be mixed with FABER POULTICE and no other product.</li> <li>Do not apply on heated surfaces</li> <li>Do not apply the product on surfaces directly exposed to sun light</li> <li>Apply the product to surfaces with a temperature of between +5 and +40°C</li> <li>When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.</li> <li>In order to achieve an even result we recommend applying the product to a larger area than the stain itself. It is advisable to apply the product on the whole tile rather than just a section of it.</li> <li>Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.</li> </ul>
EQUIPMENT CLEANING	At the end of the application, the equipment used can be washed using water.

Liquid
Clear
Characteristic
1,5 ± 0,5
1043 ± 10 g/l

## STORAGE

Keep the container tightly closed and store in a cool, dry place.

	#FABERSURFACECARE
	MADE4STONE
SHELF LIFE	24 months in the original, sealed packaging, stored in a cool, dry place.
PACKAGING	1 l bottles – 12 bottles per box
SAFETY	When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.
	Bey 50 - 27/07/2023

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the product's conditions and method of use cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

00%