

SHOWROOM LINE



Stain Removers

## OIL & GREASE REMOVER

Specific product for the removal of oil stains, and grease from surfaces made of natural stone, ceramic, terracotta, or concrete.

OIL & GREASE REMOVER is a product specifically formulated to extract and remove stains from caused by oily and greasy staining agents such as cooking oil, engine oil, mineral oil, fuels, and lubricants. The creamy, thick consistency of OIL & GREASE REMOVER increases the extractive effectiveness of the product, making it possible for it to remove deep, older and stubborn stains. It is also easy to use on vertical surfaces, thanks to its viscosity.

### **BENEFITS**

- Great stain-removal power
- Suitable for vertical application
- Easy to apply

### **USES**

Suitable for indoor and outdoor applications.

Suitable for Marble-cement agglomerate - Marble-resin agglomerate, Quartzresin agglomerate, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Cementina, Concrete, Craquelé ceramics, Glazed ceramics, Clinker, Cotto, Granite, Lapped porcelain stoneware, Polished porcelain stoneware, Natural porcelain stoneware, Textured porcelain stoneware, Cement grout, Limestone, Marble, Exposed brick, Reconstituted stone (Eco stone), Porphyry, Quarzite,

Terracotta, Travertine, Tuff

### **COVERAGE**

N.A.

### **APPLICATION EQUIPMENT**

Brush, Spatula, Direct application to stains

### **APPLICATION STEPS**

Before applying the product it is necessary to take a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material Surface Preparation

- Carefully clean the surface, making sure to remove any dust or rough dirt present.
- Never use OIL & GREASE REMOVER on wet surfaces; make sure that the surface to be treated is dry or at most, only slightly damp.
- Do not apply OIL & GREASE REMOVER to overly heated surfaces. We recommend applying the product during the coolest periods of the day.
- If the surface to be treated has a previous surface layer of wax, proceed to the removal of the same with **SOLVENT STRIPPER** or **WAX REMOVER**.

### **Application**

OIL & GREASE REMOVER va sempre utilizzato da solo, MAI miscelare assieme ad altri prodotti chimici.

- Shake well before use. Pour the product straight onto the surface being treated. Use a brush, or spatula or pour it directly onto the stain. Make sure that the whole stain is fully covered with a thick layer of product.
- Letthe product act on the surface until it is completely dry. When it dries the product turns into powder.



## SHOWROOM LINE



## APPLICATION STEPS

- Once the product is completely dry, proceed to remove the powder residue using a soft bristled broom or clean brush if treating porous material; for compact, non-absorbent materials, the residue can be removed with absorbent paper, a towel or a cloth. Once all powder residues have been removed, wipe the surface with a slightly damp cloth or mop and wait for it to dry thoroughly before assessing the stain removal results.
- If the finished result is not totally satisfactory, repeat the product application process as described above. If the stain is mixed in origin, it may be a good idea also to use another type of stain remover.

### Resume surface use

After rinsing the surface with water, wait for the floor to dry completely before opening to foot traffic.

### COMPLEMENTARY MAINTENANCE PRODUCTS

After using OIL & GREASE REMOVER evaluate if it is the case to apply a stain-proof treatment such as MARBLE & GRANITE PROTECTOR or AQUA TREATMENT, to choose based on the surface. We recommend using NEUTRAL CLEANER or FLOOR CLEANER to clean the surface on the daily. The choice depends on the type of surface.

# INSTRUCTIONS AND GUIDELINES

- OIL & GREASE REMOVER va utilizzato needs to be used on ist own. Never mix or use in conjunction with other chemicals.
- Do not apply the product on overheated surfaces
- During the application the surface can't be exposed to direct sunlight
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Apply the product to surfaces in temperatures of between +5 and +40°C
- Before applying the product it is necessary to take a preliminary test to evaluate its suitability

## **EQUIPMENT CLEANING**

The equipment used can be cleaned with water

### PHYSICAL AND TECHNICAL DATA

Formula	Thick liquid
Color	White
Odor	Solvent
Specific gravity at 20°C	$1065 \pm 20 \text{ g/l}$

**STORAGE** Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE 24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING 500 ml bottles - 12 bottles per box

ACCIDENTAL SPILLS

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.







### **SAFETY**

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

Rev6.0 - 12/09/2022

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.